

## ALUJET Glasgelege

### Product description

- ▶ The ALUJET glass scrim is a wrapping foil made from a composite aluminium material. Due to the heavy application of a polyethylene coating, it is ideal for welding to the insulating material. The ALUJET glass scrim is primarily used for laminating on mineral wool, such as glass and rock wool in felt panels, pipe shells and slatted mats, and on hard foams such as PUR and EPS.




Fig. 1: ALUJET Glasgelege

### Product benefits

- ▶ Impervious to vapours; Sd value >1,500 m; Heat-reflecting; Versatile

### Technical data

Test	Standard	Unit	Value
Material			Aluminiumsandwich
Weight	DIN 53352	g / m <sup>2</sup>	Approx. 86
Tensile elongation	DIN 52857	N / 50 mm	>250
Elongation	DIN 52857	%	Approx. 4
Heat reflection		%	Approx. 85
Sd-Value	internal	m	1.500 m

### Specification

- |                        |                   |                   |                    |
|------------------------|-------------------|-------------------|--------------------|
| Width:                 | 1.000 mm          | 1.000 mm          | 1.000 mm           |
| Length                 | 25 m              | 50 m              | 100 m              |
| m <sup>2</sup> / roll: | 25 m <sup>2</sup> | 50 m <sup>2</sup> | 100 m <sup>2</sup> |
| Width:                 | 1.200 mm          | 1.200 mm          | 1.200 mm           |
| Length:                | 25 m              | 50 m              | 100 m              |
| m <sup>2</sup> / roll  | 30 m <sup>2</sup> | 60 m <sup>2</sup> | 120 m <sup>2</sup> |

### Storage

- ▶ Without exposure to UV radiation.

### Notes



Our instructions for use, guidelines for use, product and service information and other technical specifications only serve as a guide, they only describe the properties of our products (value specifications/determinations at time of production) and services and do not constitute guaranteed characteristics. Owing to the wide-ranging areas of application of the individual products and the particular conditions (e.g. usage parameters, material properties etc.), it is incumbent on the user to test our products. Our applications engineering consulting - whether verbal, in writing or by way of tests is offered free of charge and is not legally binding.